



# SERIES TS SWITCHES

## SNAP ACTION SWITCHES - SUB-MINIATURE



### SPECIFICATIONS

Contact Rating:	0.3A @ 6VDC
Electrical Life:	50,000 cycles typical
Mechanical Life:	100,000 cycles
Insulation Resistance:	100M ohms minimum @ 100VDC
Dielectric Strength:	250 VAC for 60 seconds
Operating Temperature:	-25C to 85C
Storage Temperature:	-30C to 85C

### FEATURES & BENEFITS

- ▶ Sub miniature snap action switch
- ▶ Vertical and right angle pc pin termination

### APPLICATIONS/MARKETS

- ▶ Security/detection
- ▶ Appliance
- ▶ Instrumentation
- ▶ Power tools



### HOW TO ORDER




<b>SERIES</b> <b>TS</b>	<b>CURRENT RATING</b> 01 = 0.3A @ 6 VDC	<b>ACTUATOR BUTTON</b> 01 = Type 1	<b>OPERATING FORCE</b> F030 = 30 ± 10 gf	<b>TERMINATION</b> P = Vertical PC Pins V1 = PCB Right Angle-Short V2 = PCB Left Angle-Short V3 = PCB Right Angle-Long V4 = PCB Left Angle-Long
----------------------------	--	---------------------------------------	---	--



### Example Ordering Number

TS-01-01-F020-V1

Specifications subject to change without notice.





# SERIES TS SWITCHES

## SNAP ACTION SWITCHES - SUB-MINIATURE

TACT SWITCHES

NAVIGATION SWITCHES

PUSHBUTTON SWITCHES

TOGGLE SWITCHES

ROCKER SWITCHES

SLIDE SWITCHES

SNAP-ACTION SWITCHES

DIP SWITCHES


KEYLOCK SWITCHES

ROTARY SWITCHES

DETECTOR SWITCHES

CAP OPTIONS

### TERMINATION OPTIONS



ACTUATOR BUTTON	
Actuator	Operating Point
Type 1	6.7 ± 0.5

