

WOYR2.E121922 - Switches, Appliance and Special Use - Component

Switches, Appliance and Special Use - Component

E-SWITCH INC, DBA LAMB INDUSTRIES
7153 NORTHLAND DR N.
BROOKLYN PARK, MN 55428 United States

E121922

Investigated to ANSI/UL 61058-1

| Cat. No. | Load | Amps | Volts | Hz | Temp (°C) | Pol/ Cir | Endurance | | IP | Dis (mm) | SPCA | Std. Ed. |
|---------------------------|------|------|---------|-------|--------------|-------------|--------------|--------------|----|-------------|--------|-------------|
| | | | | | | | 30C cycle | 55C cycle | | | | |
| Appliance Switches | | | | | | | | | | | | |
| Series LS08515 | R | 10 | 125/250 | 50/60 | 25T85/55 | - | - | 10K | 40 | micro | 3A, 3B | - |
| | R | 15 | 125/250 | 50/60 | 25T85/55 | - | - | 10K | 40 | | | |
| WS10850100F130SA | R | 3 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | micro | - | 2013-02-15 |
| | GP | 3 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | | | |
| | R | 0.1 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1 | 125/250 | 50/60 | 40T85 | -2.2 | - | 10K | 67 | | | |
| | - | 0.1 | 48 | DC | 40T85 | -2.2 | - | 10K | 67 | | | |
| | - | 3 | 12 | DC | 40T85 | -2.2 | - | 10K | 67 | | | |
| WS10850100F130WA | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | micro | - | - |
| | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | - | | | |
| | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | - | | | |

| | | | | | | | | | | | | |
|--------------------------|----|--------|---------|-------|-------|---------|----|-----|----|-------|---|---|
| | GP | - | - | 50/60 | 40T85 | -2.2 | - | 10K | - | | | |
| | - | - | - | DC | 40T85 | -2.2 | - | 10K | - | | | |
| | - | - | - | DC | 40T85 | -2.2 | - | 10K | - | | | |
| WS1085300F130SA | R | 3 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | micro | - | - |
| | GP | 3 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | | | |
| | R | 0.1 | 125/250 | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1 | 125/250 | 50/60 | 40T85 | -2.2 | - | 10K | 67 | | | |
| | - | 0.1 | 48 | DC | 40T85 | -2.2 | - | 10K | 67 | | | |
| | - | 3 | 12 | DC | 40T85 | -2.2 | - | 10K | 67 | | | |
| WS1085300F130WA | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | 67 | micro | - | - |
| | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | - | | | |
| | GP | - | - | 50-60 | 40T85 | -2.2 | 6K | 10K | - | | | |
| | GP | - | - | 50/60 | 40T85 | -2.2 | - | 10K | - | | | |
| | - | - | - | DC | 40T85 | -2.2 | - | 10K | - | | | |
| | - | - | - | DC | 40T85 | -2.2 | - | 10K | - | | | |
| WS20850100F183C1A | R | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | micro | - | - |
| | R | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| WS20850100F183P1A | R | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | micro | - | - |
| | R | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |

| | | | | | | | | | | | | |
|------------------------------|----|--------|---------|-------|-------|---------|----|-----|----|-------|--------|------------|
| | GP | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| WS20850100F183S1A | R | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | micro | - | 2013-02-15 |
| | R | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1, 2 | 125-250 | 50/60 | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | GP | 0.1, 2 | 125-250 | 50/60 | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 25T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| | R | 0.1, 2 | 30 | DC | 40T85 | 1/2-2.2 | 6K | 10K | 67 | | | |
| Micro | | | | | | | | | | | | |
| WS08501 | R | 0-10 | 125-250 | 50-60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | micro | 1A, 1B | 2013-02-15 |
| WS08501 | GP | - | - | 50-60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | micro | - | - |
| | GP | - | - | 50/60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |
| WS08501 | R | 0-2 | 12 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | micro | 1A, 1B | 2013-02-15 |
| | R | 0-0.5 | 42 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |
| WS08501 | GP | - | - | 50/60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | - | - | - |
| | GP | - | - | 50/60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |
| WS08501 | R | 0-1 | 24 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | micro | 1A, 1B | 2013-02-15 |
| WS08501 f/b 00, f/b P | R | 0-10 | 125-250 | 50-60 | 25T85 | 1/2-1.2 | 6K | 10K | 67 | micro | 1A, 1B | 2013-02-15 |
| | R | 0-2 | 12 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |
| | R | 0-0.5 | 42 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |
| | R | 0-1 | 24 | DC | 25T85 | 1/2-1.2 | 6K | 10K | 67 | | | |

| Push Button | | | | | | | | | | | | |
|--------------------|----|----|-----|-------|---------|--------------|-----|-----|----|----------|--------|---|
| PB1973 | GP | - | - | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | 40 | full 2.2 | - | - |
| | GP | - | - | 50-60 | T105/55 | 2/1-1.3 | 6K | 10K | 40 | | | |
| | GP | - | - | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | 40 | | | |
| | GP | - | - | 50-60 | T105/55 | 2/1-1.3 | 6K | 10K | 40 | | | |
| Rocker | | | | | | | | | | | | |
| R1966 | GP | - | - | 50-60 | T105/55 | 1/1, 1/2-1.2 | 6K | 10K | 40 | full 1.8 | - | - |
| | GP | - | - | 50-60 | T105/55 | 1/1, 1/2-1.2 | 6K | 10K | 40 | | | |
| | GP | - | - | 50-60 | T105/55 | 1/1, 1/2-1.2 | 6K | 10K | 40 | | | |
| | GP | - | - | 50-60 | T105/55 | 1/1, 1/2-1.2 | 6K | 10K | 40 | | | |
| R1973 | GP | 12 | 125 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | full 3.5 | 3A, 3B | - |
| | R | 12 | 125 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | GP | 6 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | GP | 9 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | GP | 12 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | R | 6 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | R | 9 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | R | 12 | 250 | 50-60 | T105/55 | 1/1,2/1 | 6K | 10K | - | | | |
| | TV | 5 | 125 | 50-60 | T105/55 | 1/1,2/1 | 10K | 0K | - | | | |
| R4A | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |

| | | | | | | | | | | | | |
|------------|------|-----|-----|----|---------|---------|----|-----|----|----------|-----------|---|
| R4B | GPhp | 1 | 250 | 60 | T105/55 | 1/1-1.2 | 6K | 10K | - | full 2.5 | 2, 2A, 2B | - |
| | GP | 16 | 250 | 60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| | GPhp | 3/4 | 125 | 60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| | GP | 20 | 250 | 60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| R4C | GPhp | 1 | 250 | 60 | T105/55 | 1/2-2.2 | 6K | 10K | - | full 2.5 | 2A, 2B | - |
| | GP | 16 | 250 | 60 | T105/55 | 1/2-2.2 | 6K | 10K | - | | | |
| | GPhp | 3/4 | 125 | 60 | T105/55 | 1/2-2.2 | 6K | 10K | - | | | |
| | GP | 20 | 125 | 60 | T105/55 | 1/2-2.2 | 6K | 10K | - | | | |
| R4D | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | full 1.6 | - | - |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| R4E | GP | - | - | 60 | T105/55 | 1/2-2.2 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 1/2-2.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-2.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-2.2 | 6K | 10K | 20 | | | |
| R4F | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| R4G | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | full 1.6 | - | - |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |

| | | | | | | | | | | | | |
|------------|----|----|---------|-------|---------|---------|----|-----|----|----------|-----------|---|
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| R4H | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| R4I | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | full 1.6 | - | - |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/2-3.2 | 6K | 10K | 20 | | | |
| R4J | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 1/1-1.2 | 6K | 10K | 20 | | | |
| R5 | GP | 20 | 125,250 | 50-60 | T105/55 | 2/1-1.3 | 6K | 10K | - | full 2.5 | 2, 2A, 2B | - |
| | GP | 25 | 125,250 | 50-60 | T105/55 | 2/1-1.3 | 6K | 10K | - | | | |
| R5A | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| R5B | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |

| | | | | | | | | | | | | |
|------------|------|-----|-----|-------|---------|---------|----|-----|----|----------|--------|---|
| R5C | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| R5D | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | full 1.6 | - | - |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| R5E | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-2.4 | 6K | 10K | 20 | | | |
| R5F | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 50/60 | - | - | - | - | 00 | | | |
| R5G | GPhp | 1 | 250 | 60 | T105/55 | 2/2-3.4 | 6K | 10K | - | full 1.6 | 2A, 2B | - |
| | GP | 16 | 250 | 60 | T105/55 | 2/2-3.4 | 6K | 10K | - | | | |
| | GPhp | 3/4 | 125 | 60 | T105/55 | 2/2-3.4 | 6K | 10K | - | | | |
| | GP | 20 | 125 | 60 | T105/55 | 2/2-3.4 | 6K | 10K | - | | | |
| R5H | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | full 2.5 | - | - |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |

| | | | | | | | | | | | | |
|--------------------------|----|--------|-----|-------|---------|---------|-----|-----|----|----------|---------------|---|
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/1-1.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 50/60 | - | - | - | - | 00 | | | |
| R5I | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | full 1.6 | - | - |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| | GP | - | - | 60 | T105/55 | 2/2-3.4 | 6K | 10K | 20 | | | |
| R6 | GP | 12 | 125 | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | - | full 3.5 | 3A | - |
| | R | 12 | 125 | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| | GP | 6 | 250 | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| | R | 6 | 250 | 50-60 | T105/55 | 1/1-1.2 | 6K | 10K | - | | | |
| | TV | 5 | 125 | 50-60 | T105/55 | 1/1-1.2 | 10K | - | - | | | |
| Rocker Switch | | | | | | | | | | | | |
| RBW2A | GP | - | - | 50 | T85/55 | 2/1-1.3 | 6K | 50K | 66 | full 2 | - | - |
| | GP | - | - | 50 | T85/55 | 2/1-1.3 | 6K | 50K | 66 | | | |
| RBW2A Illuminated | GP | 16(16) | 125 | 50 | T85/55 | 2/1-1.3 | 6K | 50K | - | full | 2, A, B, C, D | - |
| | hp | 1/3 | 125 | 50 | T85/55 | 2/1-1.3 | 6K | 50K | - | | | |
| RBW2B | hp | 1/3 | 125 | 50 | T85/55 | 2/2-1.3 | 6K | 50K | - | full 2 | A, B, C, D | - |
| | GP | 16(16) | 125 | 50 | T85/55 | 2/2-1.3 | 6K | 50K | - | | | |

Investigated to ANSI/UL 1054

| Cat. No. | Amps | Volts | Hz | Load | Endur- ance | Temp (°C) | POL/ THR | Circuit Code | SPCOA |
|---|------|-------|----|------|----------------|--------------|-------------|-----------------|-------|
| 100 f/b SP, DP, 3P, 4P, f/b 1 thru 6, f/b M1, M2, M3, M5, M6, M61, M7, M71, VS2, VS3, VS5. | 5 | 125 | 60 | R | 6K | 130 | M/M | -/-A or B | A1 |

| | | | | | | | | | |
|--|-----|-----|----|---|----|-----|-----|-----------|----|
| | 2 | 250 | 60 | R | 6K | | | | |
| 100A f/b WSP or WDP, f/b 1 thru 6, may be f/b M1, M2, M6, M7, VS2 or VS3 | 5 | 120 | 60 | R | 6K | 65 | M/M | -/A, B | - |
| | 2 | 250 | 60 | R | 6K | | | | |
| 200A f/b WMSP1 thru WMSP6, WMDP1 thru WMDP3, f/b T1 or T2, f/b A1 or A2, f/b M2, M6, M61, M7, VS2, f/b Q or R, f/b E | 3 | 120 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 1.5 | 250 | 60 | R | 6K | | | | |
| 200A f/b WMSP1, WMSP2, WMSP3, WMSP4, WMSP5, WMSP6, WMDP1, WMDP2, WMDP3, f/b T1 or T2, f/b A1, f/b M2, M6, M61, M7 or VS2, f/b Q, f/b E f/b 200B, f/b WMSP1, f/b T2 or A1, f/b S, f/b M6, f/b Q, f/b E | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| 200B f/b WMSP3 thru WMSP5, f/b T2, f/b A1, f/b SM6, f/b Q or R, f/b E | 3 | 120 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 1.5 | 250 | 60 | R | 6K | | | | |
| 200MSP f/b 1, 2, 3, 4, 5 or 6. 200 MDP f/b 1, 2, or 3 | 1 | 250 | 60 | R | 6K | 130 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| 300 f/b SP, DP, 3P or 4P, f/b 1 thru 6, f/b M1, M2, M3, M5, M6, M7, VS2, VS3, VS4 or VS5. | 5 | 120 | 60 | R | 6K | 60 | M/M | -/-A or B | A1 |
| | 2 | 250 | 60 | R | 6K | | | | |
| 300A f/b WSP, WDP, W3P, f/b 1 thru 6, f/b R1, R2, R11, R16, J1, J2, J3, J4, J4, J5, J6, f/b 3 letters, f/b M1, M2, M3, M6, M7, VS2, VS3, V2N | 5 | 120 | 60 | R | 6K | 65 | M/M | -/A, B | - |
| | 2 | 250 | 60 | R | 6K | | | | |
| 400A f/b WMSP1 thru WMSP5, WMDP1 thru WMDP3, f/b R1, f/b BLK, RED, WHT, f/b M1, M2, M6, M61, M7, M71, VS2, VS21, f/b Q or R, f/b E | 3 | 120 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 1.5 | 250 | 60 | R | 6K | | | | |
| 400A f/b WMSP1, WMSP2, WMSP3, WMSP4, WMSP5, WMSP6, WMDP1, WMDP2, WMDP3, f/b R1 f/b M1, M2, M6, M7 or VS2, f/b Q, f/b E f/b 400B, f/b WMSP1, f/b R1, f/b MT or MZ | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/-A or B | - |
| | 3 | 120 | 60 | R | 6K | | | | |

| | | | | | | | | | |
|---|-----|-----|----|----|----|----|---------------|-------|---|
| 400B f/b WMSP1 thru WMSP5, f/b R2, f/b BLK, f/b SM6, f/b Q or R, f/b E | 3 | 120 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 1.5 | 250 | 60 | R | 6K | | | | |
| 400MSP f/b 1, 2, 3, 4, 5 or 6. 400 MDP f/b 1, 2 or 3 | 1 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| 500ASSP1 f/b M2 or M6 | 3 | 120 | 60 | R | 6K | 65 | 1/1 or 1/2 | -/-/A | - |
| | 1 | 250 | 60 | R | 6K | | | | |
| 500ASSP3 f/b M2 or M6 | 1.5 | 250 | 60 | R | 6K | 65 | 2/1 or 2/2 | -/-/B | - |
| | 3 | 125 | 60 | R | 6K | | | | |
| 500S f/b DP or SP f/b 1, 2 or 3, f/b M1, M2, M6, M7 or VS2 | 5 | 120 | 60 | R | 6K | 65 | 1/2 or 2/2 | -/-/B | - |
| | 2 | 250 | 60 | R | 6K | | | | |
| 700 f/b SP7 or DP7, f/b M1. | 3 | 120 | 60 | R | 6K | 65 | M/M | -/-/B | - |
| | 1 | 250 | 60 | R | 6K | | | | |
| 800A f/b WSP8 or WSP9, f/b M1, M2, M6, M61, M7, or VS2 | 3 | 120 | 60 | R | 6K | 75 | 1/1 | -/-/A | - |
| | 1 | 250 | 60 | R | 6K | | | | |
| 800SP9, 800SP8 | 1 | 250 | 60 | R | 6K | 75 | 1/1 | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| D-16 | 0.2 | 250 | DC | - | 6K | 55 | M/2 | PP/- | - |
| | 6 | 24 | DC | - | 6K | | | | |
| | 8 | 125 | 60 | GP | 6K | | | | |
| | 5 | 250 | 60 | GP | 6K | | | | |
| KO 113A, KO 113B, KO 113C | 4 | 120 | 60 | GP | 6K | 55 | 1/1 | -/- | - |
| | 2 | 250 | 60 | GP | 6K | | | | |

| | | | | | | | | | |
|---|----|-----|----|-------|-----|-----|-----|------|--------------|
| KO 113D | 4 | 120 | 60 | GP | 6K | 55 | 1/1 | -/- | - |
| | 2 | 250 | 60 | GP | 6K | | | | |
| KO 128 f/b A, B, C, E, F, G, H | 4 | 125 | 60 | GP | 6K | 55 | 1/1 | -/- | - |
| | 2 | 250 | 60 | GP | 6K | | | | |
| KO 129, KO 130 | 4 | 125 | 60 | GP | 6K | 105 | M/M | PP/- | - |
| | 4 | 28 | DC | - | 6K | | | | |
| | 2 | 250 | 60 | GP | 6K | | | | |
| LS f/b -00 thru -99, f/b C1, C2 | 15 | 125 | 60 | R | 10K | 85 | 1/1 | -/- | Note 5 |
| | 15 | 250 | 60 | R | 10K | | | | |
| LS08515 F/b 00 through 99 to represent actuating level, -00 means None, f/b C1 or C2 for quick-connected terminal. | 15 | 125 | 60 | R | 10K | 85 | 1/1 | -/- | Note 5 |
| | 15 | 250 | 60 | R | 10K | | | | |
| MS Series | 5 | 125 | 60 | GP | 10K | 75 | 1/2 | -/- | Note 5 |
| | 5 | 250 | 60 | GP | 10K | | | | |
| MS08505 F/b Lever type 00, 01, 02, 03, or 05, f/b F, f/b 3 for Operating Force, f/b S1 or P1 for Terminal Type. | 5 | 125 | 60 | GP | 10K | 75 | 1/2 | -/- | Note 5 |
| | 5 | 250 | 60 | GP | 10K | | | | |
| R1966 or R19A | 6 | 250 | 60 | GP | 6K | 65 | 1/M | PP/- | 3 |
| | 15 | 125 | 60 | GP | 6K | | | | |
| | 8 | 250 | 60 | GP | 6K | | | | |
| R3070 or R30 | 15 | 125 | 60 | GP | 6K | 65 | 1/1 | -/- | 2, 3, Note 1 |
| | 10 | 250 | 60 | GP | 6K | | | | |
| R4 | 20 | 125 | 60 | 3/4hp | 6K | 65 | 1/M | -/- | 3 |
| | 16 | 250 | 60 | 1hp | 6K | | | | |

| | | | | | | | | | |
|--|-----|---------|-------|----|-----|----|-----|-------|-----------|
| R4, R5 f/b A, B, C, E, F, H | 20 | 125 | 60 | GP | 6K | 65 | M/M | -/- | - |
| | 15 | 250 | 60 | GP | 6K | | | | |
| R4, R5 f/b D, G or I | 15 | 125 | 60 | GP | 6K | 65 | M/M | -/- | - |
| | 10 | 250 | 60 | GP | 6K | | | | |
| RP3508 f/b A or B, may be f/b L | 3 | 125 | 60 | GP | 6K | 85 | 1/1 | -/- | Note 6 |
| | 1.5 | 250 | 60 | GP | 6K | | | | |
| RR3112 f/b A, B, BW, C, D, L or LP, f/b 01 or 02 | 16 | 125 | 60 | GP | 6K | 85 | 1/M | -/- | Note 1, 4 |
| | 10 | 250 | 60 | GP | 6K | | | | |
| RR3130 f/b A, B or C | 10 | 125-250 | 60 | GP | 6K | 65 | 2/M | PP/- | 2 |
| | 6 | 125-250 | 60 | GP | 6K | | | | |
| RR3402 f/b A, C or D | 6 | 125 | 60 | GP | 6K | 55 | 1/M | -/- | - |
| | 3 | 250 | 60 | GP | 6K | | | | |
| SS07503 Followed by -00 thru -03 representing actuating level, -00 means None, f/b P1, V1 or V2 for quick-connected terminal. | 3 | 125 | 60 | GP | 10K | 75 | 1/2 | -/- | - |
| | 1.5 | 250 | 60 | GP | 10K | | | | |
| ULV4F f/b 2, f/b 3, B, G or H, f/b N, S or 1, f/b N, S or 1, f/b none or G, f/b none, 2, 3 or 5, f/b none, 0, 1, 2, 3, 4, 5, G or P, f/b none, 1, 3, 4, 5, 6 or 7 | 3 | 125-250 | 50/60 | R | 50K | 65 | 2/2 | -/A,B | Note 6 |
| ULV4F2GSSDF | 3 | 125-250 | 50/60 | R | 50K | 65 | 2/2 | -/A,B | Note 6 |
| ULV7F f/b 2, f/b 3, B, G or H, f/b S or 1, f/b S or 1, f/b none or G, f/b 3 or 6, f/b 0, 1, 2, 3, 4, 5, G or P, f/b 1, 3, 4, 5, 6 or 7 | 3 | 125-250 | 50/60 | R | 50K | 65 | 2/2 | -/A,B | Note 6 |
| ULV8F f/b 2, f/b 3, B, G or H, f/b S or 1, f/b S or 1, f/b none or G, f/b 3, f/b 0, 1, 2, 3, 4, 5, G or P, f/b 1, 3, 4, 5, 6 or 7 | 3 | 125-250 | 50/60 | R | 50K | 65 | 2/2 | -/A,B | Note 6 |
| WMDP1 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |

| | | | | | | | | | |
|---|-----|-----|----|---|----|----|-----|-----|---|
| | 3 | 120 | 60 | R | 6K | | | | |
| WMDP2 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMDP3 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMDP6 may be f/b T1 or T2, f/b A1, f/b M2, M6, M61, M7 or VS2, f/b Q, f/b E, f/b 200B, f/b WMSP1 f/b T2 or A1, f/b SM6, f/b Q, f/b E or may be f/b R1, f/b M1, M2, M6, M7 or VS2, f/b Q, f/b E, /b 400B, f/b WMSP1, f/b R1, f/b MT or MZ | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP1 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP2 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP3 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP4 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP5 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |
| WMSP6 | 1.5 | 250 | 60 | R | 6K | 65 | M/M | -/- | - |
| | 3 | 120 | 60 | R | 6K | | | | |

A1 - These switches should not be operated under more one load in the end-product.

Note 1 - The suitability of the actuator button material as an enclosure has not been investigated.

Note 2 - Terminations other than solder connections should be evaluated for compliance with the end-use product standard.

Note 3 - This switch has been investigated only for voltage changing and is not intended to be operated under load.


Note 4 - These switches employ a lamp that is powered by a separate DC source. Lamp DC source should be evaluated for compliance with the end-use standard.

Note 5 - The switch was subjected to a minimum 10,000 cycle endurance Test.

Note 6 - These switches may be provided with a light. Lamp life has not been evaluated.

Note 7 - These are lighted switches employing a lamp. The lamp life should be evaluated when required by the end-use product Standard.

Note 8 - Model PB1973 is provided with an additional set of contacts in switch body for illuminate using. The contacts were not tested, and the suitability of the contacts shall be determined in the end-product appliances.

Marking: Company name or trademark , ,  E-SWITCH®, ,  E-SWITCH®,  LAMB,  LAMB,  LAMB INDUSTRIES, catalog, model Or part number, electrical ratings and the Recognized Component Mark,  On the product Or On the smallest unit container In which the product Is packaged.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."