

ECM3022 SERIES FREE HANGING PLUG HOUSING



SPECIFICATIONS

Voltage Rating: 250VAC
Current Rating: 5A max
Housing: PA66, UL94V-0
Insulation Resistance: 100Mohm min
Withstanding: 100Mohm min
Operating Temperature: -25°C to +85°C
Poles: 2-10
Wire Range: 28-22AWG

FEATURES & BENEFITS

Free Hanging 3mm spacing
Wire to Wire Receptacle to Plug system
Compatible with ECM3025 Series
Low Profile Design
2 to 10 Poles
ECM5558M2822C - male

PART NUMBER CONFIGURATOR

Series



ECM3022

Function



02 - 2 Pins
04 - 4 Pins
06 - 6 Pins
10 - 10 Pins

Color



R - Red

Terminal Type



P - 28-22AWG Pin


NOTES:

Specifications based on using ESW Crimp Terminals (Sold Separately)





Specifications subject to change without notice 5/16/2025

ECM3022 SERIES FREE HANGING PLUG HOUSING

BODY AND TERMINAL DIMENSIONS



OBJECT NAME	NO. OF POS.	DIM "X"
ECM302202R	2	3.85 [.152 in]
ECM302204R	4	7.00 [.276 in]
ECM302206R	6	10.00 [.394 in]
ECM302210R	10	16.00 [.630 in]



ECM3022 SERIES FREE HANGING PLUG HOUSING

PIN POSITIONS

